

HDM-C6MWIP4K-SET

HDMI H.264 IP MATRIX DECODER/ENCODER OVER CAT/X WITH VIDEO WALL MODE SUPPORT



IP Video wall Decoder/Encoder

M-Series Latency Table

SOURCE RESOLUTION	ADVANCED SETTINGS	OUTPUT RESOLUTION	LATENCY
Resolutions under 1920x1080 YUV 4:4:4 8-bit	Default	Resolutions under 1920x1080	<50ms
	"Low Delay"	1920x1080	<50ms
	"High Quality"	YUV 4:4:4 8-bit	<50ms
1920x1080@60Hz RGB 8-bit	Default	Resolutions under 1920x1080	<80ms
	"Low Delay"	1920x1080	<80ms
	"High Quality"	YUV 4:4:4 8-bit	<80ms
1920x1080@60Hz RGB 8-bit	Default	1920x1080@60Hz	~100ms
	"Low Delay"	YUV 4:4:4 8-bit	~50ms
	"High Quality"	YUV 4:4:4 8-bit	~100ms
1920x1080@60Hz RGB 8-bit	Default	1920x1200@60Hz	~100ms
	"Low Delay"	YUV 4:4:4 8-bit	~50ms
	"High Quality"	YUV 4:4:4 8-bit	~100ms
1920x1080@60Hz RGB 8-bit	Default	3840x2160@30Hz RGB 8-bit	~200ms
	"Low Delay"	3840x2160@30Hz RGB 8-bit	~100ms
	"High Quality"	3840x2160@30Hz RGB 8-bit	~200ms
1920x1080@60Hz RGB 8-bit	Default	3840x2160@60Hz RGB 8-bit	~6000-12000ms
	"Low Delay"	3840x2160@60Hz RGB 8-bit	~300ms
	"High Quality"	3840x2160@60Hz RGB 8-bit	~6000-12000ms
3840x2160@30Hz YUV 4:4:4 8-bit	Default	Resolutions under 1920x1080	~100ms
	"Low Delay"	1920x1080	~50ms
	"High Quality"	YUV 4:4:4 8-bit	~100ms
3840x2160@30Hz YUV 4:4:4 8-bit	Default	1920x1080@60Hz	~150ms
	"Low Delay"	YUV 4:4:4 8-bit	~100ms
	"High Quality"	YUV 4:4:4 8-bit	~150ms
3840x2160@30Hz YUV 4:4:4 8-bit	Default	1920x1200@60Hz	~200ms
	"Low Delay"	YUV 4:4:4 8-bit	~150ms
	"High Quality"	YUV 4:4:4 8-bit	~200ms
3840x2160@30Hz YUV 4:4:4 8-bit	Default	3840x2160@30Hz RGB 8-bit	~200ms
	"Low Delay"	3840x2160@30Hz RGB 8-bit	~100ms
	"High Quality"	3840x2160@30Hz RGB 8-bit	~200ms
3840x2160@30Hz YUV 4:4:4 8-bit	Default	3840x2160@60Hz RGB 8-bit	~300ms
	"Low Delay"	3840x2160@60Hz RGB 8-bit	~200ms
	"High Quality"	3840x2160@60Hz RGB 8-bit	~300ms

Values given are an approximation only and are subject to network conditions