

Model #: FO-HDM-IP4K-SET

HDMI Extender up to 20KM
over Fiber Optic with IR Support



4K HDMI EXTENDER CABLE OVER FIBER OPTIC

KEY FEATURES

2.4.1 Front Panel (Transmitter, FO-HDM-IP4K-S)




1. POWER LED: LED lights red when device is powered on	2. DC 5V: Connect the 5 V DC power supply included.
3. DATA LED: When data is transmitting from the source the led will continuously flash YELLOW	4. LINK LED: When connected to RX or network switch the LED will light GREEN.
5. OPTICAL OUT: Connect SC single mode fiber optic cable.	

2.4.2 Front/Rear Panel (Transmitter, FO-HDM-IP4K-R)



1. POWER LED: LED light red when powered on	2. DC 5V: Connect 5VDC powers supply included
3. DATA LED: Flashes yellow when transmitting data	




1. HDMI OUT: Connect to HDMI source via HDMI Cable.	2. IR IN: Plug the IR Blaster cable for IR signal being transmitted. place IR Blaster within direct site of the device being controlled.
3. RESET: To reset the unit when no link is established.	

FO-HDM-IP4K-SET

CABLE INDEX
■ INPUT/OUTPUT
■ SC FIBER OM2/3
■ IR CONTROL

1080p = 20Km (2000m) OM2/3 SINGLE MODE
 4K30p = 20Km (2000m) OM2/3 SINGLE MODE
 Application Diagram 1
 POINT TO POINT



ITEM	SPECIFICATION	
Model	FO-HDM-IP4K-S	FO-HDM4K-XX-MM (Receiver)
Description	HDMI Type A (male)	HDMI Type A (female)
HDMI Standard	HDMI 2.0	
HDCP Compliant	Yes	
Video Bandwidth	18 Gbps	
Supported Resolution	Full HD 1080p@50/60Hz, 4K (3840x2160@60Hz), 4K UHD (4096x2160@60Hz)	
Distance	20mm - 30mm - 40mm - 60mm	
Audio Support	Surround Sound (up to 7.1 Ch) or Stereo Digital Audio	
Optical Source	850nm VCSEL - 50/125 μm Multi-mode glass-fiber	
EDID Transmission	Real Time EDID Transmission	
Type of Fiber	Fiber+Copper Hybrid	
Dimensions (LxWxH)	114@x 25W x 20H(mm)	73@x 25W x 21H(mm)
Weight	From 3.7 lbs	
Power Supply	5V/2A	
Power Consumption	0.3W(Typ)	1.39W(Typ)
Operating Temperature	32° ~ 122°F (0° to 50°C)	
Storage Temperature	-4° ~ 158°F (-20° ~ 70°C) 20~90% RH (no condensation)	



VIDEO WALL VIDEO PROCESSORS
 MULTIVIEWERS DIGITAL SIGNAGE
 EXTENDERS CONTROL CENTERS
 SCALERS WIRELESS



Toll Free 1.866.508.0269 | sales@avenview.com